


## Mito sospeso move 40 up datasheet

Annular LED suspended and ceiling luminaire with double-sided light emission and a diameter of 40 cm. There is a choice of two lighting effects. table (wide) for use over tables - wide light beam downwards and upwards. room (narrow) for freely suspended luminaire lighting - concentrated light beam directed downwards, diffused light directed upwards.

The suspension length is continuously, electrically adjustable from 50 to  $200\,\mathrm{cm}$ .

Version with integrated power supply unit for mounting on plaster surfaces; connection to 230 V AC mains voltage. Can be controlled via »touchless control « (gesture control on the head) or Occhio air. The color temperature can be continuously controlled via »touchless control« or Occhio air from 2700 to 4000 K (optional 2200 to 3500 K).





technical	data	Mito	sospeso	move	40 up

properties material		aluminium, painted, PVD-coated steel, plastic, optical silicone, fibreglass			
	height adjustment (electronic only)	500-2000 mm (variable, not designed for continuous operation)			
	weight	4.7 kg			
surface head		bronze, matt gold, rose gold, matt silver, matt white, matt black, phantom, black phantom			
	canopy	matt white, matt black			
Occhio »color tune« LED	average life time	> 50.000 hrs			
	energy efficiency class (luminous efficiency)	G (59 lm/W)			
	power	LED 40 W (incl. Occhio power supply unit 46 W, standby < 0.5 W)			
	color rendering index	high color; CRI Ra 95			
	color temperature (color consistency)	2700-4000 K (2-step)	2200-3500 K (2-step 2200 K, 3-step 3500 K)		
electricity	dimming	via »touchless control« or Occhio air			
	connection	230 V AC			
	power factor power supply (cos φ1)	0.9			
	flicker/stroboscopic effect	1 (PstLM) / 0.9 (SVM)			
	permitted operating conditions	max. 30°C for indoor use only			








# Mito sospeso move 40 up lighting effects






### table (wide)


wide light beam (up and down), beam angle approx. 80° (down)

inserts: wide/flood

luminous flux : high color 40 W 2220 lm

UGR (4H8H) < 19





room (narrow) concentrated light downwards, beam angle approx. 50°, diffuse upwards

inserts: narrow/diffuse

luminous flux: high color 40 W 2140 lm

UGR (4H8H) < 19